



## Applications

Grass and synthetic line marking for sports venues utilising specialist water based paints.

Application of chemical fertilizers and pesticides using optional attachments.



## Features

Features in **BOLD** are additions to standard IGO

- Pedestrian powered spray linermarker.
- Pre-set adjustment to 2", 3", 4", 5" and 6" line widths.
- Extendable sliding front chassis.
- **Lever operated disc lifter facility.**
- **Solenoid spray control for instant 'shut off'.**
- Built in battery condition ammeter.
- Connection box with integrated overload and reset trip.
- Pneumatic tyres with improved tread for low mud pick up.
- 12v bypass pump with output up to 3.78 ltrs per minute dependent on nozzle type and size.
- Simple to prime, spray and clean.
- Easy assembly on delivery.
- All protective covers manufactured from rotational moulded MDPE



## DIMENSIONS:

**MACHINE:**

(With handlebars at max height)  
L 1120 x W 675 x H 1060mm

(With handlebars removed and stowed for shipment)  
L 890 x W 675 x H 430mm

**SHIPPING CARTON:**

L925 x W715 x H440mm

**WEIGHT:**

Approx 34 - 36kg

Manufactured in the UK by Linemark (UK) Ltd.  
Rawtenstall.BB4 6JB

**Technical specifications**

- **CHASSIS:**  
22.2mm x 1.2gauge zinc plated, tubular steel construction.
- **BATTERY:**  
12Volt 20AH leak proof sealed lead acid, complete with male spade terminals and protective terminal 'boots'.
- **CHARGER:**  
12VDC - 2.3amp. Complete with connection box plug and additional crocodile clips for off-machine charging.
- **SWITCH:**  
SPDT alternative action button, fixed in zinc plated housing on handle bar with weatherproof cable terminating in plastic connection box plug.
- **PUMP:**  
12VDC - 7.5amp 50psi bypass pump. Open flow 3.78 ltrs pm
- **CONNECTION BOX:**  
Precision made connection box protected by 7.5amp rated anti surge PCB .
- **WHEELS:**  
Plastic centre with 260mm x 85mm pneumatic tyre with linear ribbed tread. Max pressure 2.0 bar - 30psi

